

# TW125B

NavtechGPS

+1-703-256-8900 or 800-628-0885  
info@NavtechGPS.com  
www.NavtechGPS.com

**CALIAN**  
Confidence. Engineered.

## 27 dB GNSS In-Line Amplifier (Low Current)

Frequency Coverage: Full GNSS Spectrum

The TW125B is a low cost, rugged, waterproof, low noise, low current/low voltage, 1.1 to 1.7 GHz band, 27 dB gain inline amplifier, specially designed to amplify all GNSS frequency signals, from GPS L5 to GLONASS G1.

The TW125B provides for much longer cable runs from antenna to receiver, for applications such as mastmount, large vehicle and timing systems, without degradation of system sensitivity.

Its low loading allows for both the antenna and the TW125B in-line amplifier to be powered by the GNSS receiver.

The TW125B passes DC supply to the antenna, therefore not requiring additional hardware such as bias-T, power cable and power supply.

Amplifiers are directional and must be installed in the orientation indicated on the product label (arrow points away from antenna).



### Applications

- All GNSS Signals – GPS, GLONASS, Galileo, BeiDou & SBAS
- Commercial, Industrial and Military Telematics Systems
- Wireless and Telecom Timing and Synchronization Applications

### Features

- Low Current / low voltage
- Very low noise figure
- Wide input voltage 3 to 16 Volts
- Nickel-plated brass, IP67 compliant housing
- Powered via antenna coax from receiver
- 50 Ohm port impedance
- Available SMA, TNC, and N-Type jack connectors
- CE RED, REACH, and RoHS compliant

### Benefits

- Improves signal reception
- Enables extended cable runs
- Avoid installation of costly low-loss cable
- Fits in line with antenna cable
- No external DC power supply required
- Easy to install - mounting clamp included

NavtechGPS

Contact NavtechGPS for product details. [www.NavtechGPS.com](http://www.NavtechGPS.com)  
+1-703-256-8900 • 800-628-0885 • [info@navtechgps.com](mailto:info@navtechgps.com)

# 27 dB GNSS In-Line Amplifier (Low Current)

Frequency Coverage: Full GNSS Spectrum

## Electrical Specifications

Parameter	Value
<b>Operational Frequency</b>	1.1 to 1.7 GHz
<b>I/O VSWR (50 Ω)</b>	1.5 typ., 2 max.
<b>Gain and Flatness</b>	27 dB typ., 26 dB min., ±0.5 dB ripple
<b>Noise Figure</b>	2 dB typ.
<b>Supply Current</b>	11 mA typ.
<b>Out-of-band Rejection</b>	-
<b>Reverse Isolation</b>	35 dB min.
<b>Supply Voltage Range</b>	3 to 12 VDC nominal
<b>Output P1dB (Compression Level)</b>	+9 dBm
<b>Output IP3</b>	+14 dBm
<b>Maximum Input RF Power</b>	-
<b>Group Delay Variation</b>	-

## Mechanicals

Size	59 mm (L.) x 20 mm (dia.)
Weight	85 g
Enclosure	Nickel-plated brass
Mount	-
Connectors	SMA, TNC, or type-N (female)

## Environmental

Operating Temperature	-40 °C to 85 °C
Storage Temperature	-55 °C to 95 °C
Vibration	-
Shock	-
Salt Fog	-
IP Rating	IP67
Compliance	CE RED, RoHS, and REACH compliant

## Warranty

Parts and Labour	-
------------------	---

## Ordering Information

**Part Number** **32-0125B-xx**

Where xx = 00 for SMA (female), 01 for TNC (female) or 14 for type-N (female)

Please refer to our **Ordering Guide** to review available radomes and connectors at:

<https://www.tallysman.com/resource/tallysman-ordering-guide/>

## Mechanical Diagram - Units in 'mm'

